



21D64-2

HOTROD™ SERIES UNIVERSAL NITRIDE IGNITOR UPGRADES

120V nitride upgrade kits for conversion of silicon carbide (flat or spiral).

FEATURES

- HotRod™ replaces over 170 ignitors; HotRod EX™ replaces over 260 ignitor models
- Robust nitride ignitor design for longer life and fewer callbacks – 5-year warranty
- Nitride ignitors with 14.5" and 15.5" lead-stripped ends
- Universal and standard mounting brackets and 2 ceramic wire nuts
- Replaces most silicon carbide ignitors, including many Carborundum™ models

SPECIFICATIONS

| | |
|--|--------------------------|
| Operating Voltage..... | 102-132 VAC, 60 Hz |
| Max. Load Current | 3.0 A @ 132 VAC, 25°C |
| Warmup Time | 21D64-2: 17 sec. minimum |
| | 21D64-44: 8 sec. minimum |
| Temperature Rating Lead Insulation | 250°C |

HOTROD™ 21D64 SERIES UNIVERSAL IGNITOR UPGRADES

| DESCRIPTION | LEAD LENGTH | MODEL NUMBER | ITEM NUMBER |
|---|-------------|--------------|-------------|
| HotRod Kit includes 120V nitride ignitor, 2 brackets (one universal), 15.5" lead-stripped ends, ceramic wire nuts and mounting screw | 15.5" | 21D64-2 | 21D64 002 |
| HotRod 5-pack contains 5 single-pack ignitor kits | 15.5" | 21D64-5PK | 21D64-5PK |
| HotRod EX Kit includes 120V nitride ignitor, 2 brackets (one universal), 14.5" lead-stripped ends, ceramic wire nuts and mounting screw | 14.5" | 21D64-44 | 21D64-44 |

FLAME SENSOR AND HOT ROD COMBO

| DESCRIPTION | LEAD LENGTH | MODEL NUMBER | ITEM NUMBER |
|--|-------------|--------------|-------------|
| HotRod Combo, universal ignitor and flame sensor | 15.5" / 30" | 21D64C-843 | 21D64C-843 |

