

Airow 3 Hydrogen Peroxide Air Cleaner



Bel-Aire

ElectronicAirCleaners.com

TADIRAN Airow 3™ is a unique Hydrogen Peroxide Air Treatment System designed to reduce airborne pathogens in your home. With its robust design and effective air treatment capabilities, Airow 3 reduces SARS-CoV-2, viruses, bacteria, and mold* to promote a healthier indoor environment. Specifically designed for mini-split AC systems and ceiling cassettes, Airow 3 safely operates without emitting ions, requires no maintenance, and is incredibly easy to install with its plug-and-play functionality.

Features

- Reduces up to 99% of bacteria, viruses, and mold
- FDA-cleared testing lab has thoroughly tested and approved its effectiveness
- Utilizes best-in-class air treatment technology, taking a proactive approach to treat the air
- Requires zero maintenance and no upkeep, ensuring a hassle-free operation
- Maintains lasting effectiveness, even when the AC system is turned off
- Simple installation process for convenient setup
- Applicable in various settings: residential homes, commercial spaces, schools, new construction, hotels, senior living facilities, and more
- Zero Ozone



 **FIELDCONTROLS**
AIR TREATMENT



252.522.3031
fieldcontrols.com
sales@fieldcontrols.com

How It Works

TADIRAN AIROW 3™ uses a discharge current to break apart Oxygen (O₂) molecules into two separate O atoms. The free oxygen atoms combine with water (H₂O) molecules in the airflow and transform into purifying Hydrogen Peroxide (H₂O₂). The H₂O₂ is then distributed into the indoor space by the air conditioning unit. When the H₂O₂ encounters viruses, bacteria, mold, or other airborne contaminants, it breaks down the exterior structures, thus inactivating and reducing aerosol pathogens.



Backed By Science

Bioaerosol Type	Species/Protocol	Testing Lab	Results
Bacteria	Streptococcus pyogenes (Group A) Chamber size: 36m ³ , after 120 min	Innovative Bioanalysis Labs, USA	100% ²
	Staphylococcus Epidermis vegetative (+) Chamber size: 1m ³ , after 60 min	Aerosol Research and Engineering Laboratories, USA	99.994% ⁹
Virus	SARS-CoV-2 Chamber size: 16m ³ , after 60 min	Innovative Bioanalysis Labs, USA	99.93% ⁷
Virus	RNA Virus MS2 Bacteriophage Chamber size: 1m ³ , after 60 min	Aerosol Research and Engineering Laboratories, USA	99.994% ⁸
Mold Spore	Blue Mold (Penicillium Citrinum) Aerosolized Chamber size: 25m ³ , after only 3 hours	Kitazao Laboratory, Japan	99.4% ¹⁰
Ozone Emission	UL 867 Section 40	INTERTEK	<5 ppb ⁵ Tested

- ¹ TADIRAN AIROW 3 device was tested in the US-based internationally recognized laboratory Innovative Bioanalysis, which is BSL3 accredited.
- ² TADIRAN AIROW 3 reduced the aerosol of Streptococcus pyogenes in 36 cubic meter test chamber, by 100% within 120 min.
- ³ Independent tests commissioned by Tadiran showed that TADIRAN AIROW™ technology eliminated known aerosolized pathogens under optimal testing conditions. To learn more about the tests, visit www.tadiran-international.com/scientific-testing.
- ⁴ Only qualified and licensed HVAC technicians may install TADIRAN AIROW.
- ⁵ TADIRAN AIROW is verified as zero ozone. Does not emit more than 0.005PPM as tested per UL 867.
- ⁶ World Health Organization EPA report on the environment <https://www.epa.gov/report-environment/indoor-air-quality>. Pre COVID-19.
- ⁷ TADIRAN AIROW 3 reduced detected SARS-CoV-2 aerosol levels by 99.93% within 1 hour (16 cubic meter test chamber).
- ⁸ TADIRAN AIROW 3 reduced MS2 levels by 99.994% in 1 hour (1 cubic meter test chamber).
- ⁹ TADIRAN AIROW 3 reduced detected Bacteria Staphylococcus epidermidis aerosol levels by 99.994% within 1 hour (1 cubic meter test chamber)
- ¹⁰ TADIRAN AIROW 3 reduced Aerosol of Blue Mold by 99.4% within 3 hours in a 25m³ chamber.
- ¹¹ TADIRAN AIROW 3 creates <15 ppb H₂O₂ based on a test conducted by LSC Laboratory inc.
- ¹² TADIRAN AIROW 3, tested by TUV and Intertek, does not emit more than 0.005PPM.
- ¹³ All pictures shown are for illustration purposes only. Actual product may vary.

