special HD calclean®



FOR CLEANING ELECTRONIC AIR FILTERS AND EVAPORATOR COILS WHICH RESIST CLEANING WITH OTHER DETERGENTS

For Professional Use Only

net contents: 1 U.S. Gal. (3.785 liters)



St. Louis, MO 63146

THIS PRODUCT HAS BEEN AUTHORIZED BY THE U.S.D.A. FOR USE IN FEDERALLY INSPECTED MEAT AND POULTRY PLANTS.

CALGON is a licensed trade name

WARNING: Contains Potassium Hydroxide. (CAS# 1310-58-3). CAUSES IRRITATION. HARM-FUL IF SWALLOWED. Do not get in eyes, on skin or clothing. Keep container closed. Wash thoroughly after handling.

FIRST AID: Eyes: In case of contact, flush with plenty of water for at least 15 minutes. Call a physician. Skin: In case of contact, flush with plenty of water for at least 15 minutes. If irritation develops, Call a physician. Internal: If swallowed, do NOT induce vomiting. Give large quantities of water. Never give anything by mouth to an unconscious person. Call a physician.

DIRECTIONS FOR CLEANING ELECTRONIC AIR FILTERS

1. Turn the unit and fans off.

2. When using the No. 300P Poly Sprayer, prepare cleaning solution in sprayer tank by mixing 1 part of Special HD CalClean to 5 parts of water, adding the water to the sprayer tank first. Or, you may use the Nu-Calgon Wholesaler, Inc. "hose-end" sprayer, the Coil Gun, and set the sprayer at its 6:1 ratio setting.

3. Spray the cleaning solution on the plates. Be sure to get all surfaces of the plates wet with the cleaning solution.

4. Allow the solution to remain on the plates 5 to 15 minutes.

5. Rinsing, If using the 300P Poly Sprayer, use a separate water source for rinsing. If the unit is equipped with spray nozzles for washing, they can be used for rinsing. Use hot water if available.

6. On very dirty units it may be necessary to repeat steps 3, 4 and 5. NOTE: Do not use the Special HD undiluted or any stronger than 1 part

cleaner to 3 parts water.