Skuttle®
Indoor Air Quality Products

Humidifier Comparison Chart

Bel-Aire
ElectronicAirCleaners.com

Contractor Humidifier Application and Sizing Information

Humidifier Type	Skuttle Humidifier	Tight House	Average House	Loose House	Heating System Type: Gas Forced Air System	Gas High Efficiency Forced Air System	Electric Forced Air System	Heat Pump, Geothermal or Solar Forced Air System	Oil Fired Forced Air System	Hydronic System	Wood Fired Forced Air System	Coal Fired Forced Air System	Baseboard or Radiant Electric	Competitive Model Comparisons			
Flow Thru	2000	3333	2121	1627		X	X*	X**	X**	X						G200	550	HE220	
	2001	4285	2725	1955		X	X*	X**	X**	X					1042 & 1099		560 & 440	HE260	
	2002	4525	2880	2065		X	X*	X*	X**	X					1137	G100	760	HE360	
		4760	3030	2175		X	X	X	X	X									
Steam Type	55-UD	3095	1970	1415		X	X	X	X	X									
	F60-1	3095	1970	1415		X	X	X	X	X								HE420	
	60-2	4045	2575	1845		X	X	X	X	X									
	F60-2	4045	2575	1845		X	X	X	X	X								HE460	
	60-BC1	3095	1970	1415		X	X	X	X	X	X	X	X	X					
Spray Type	592-9	2850	1800	1300			X	X	X										
	592-22	2850	1800	1300		X				X						50			
Drum Type	190	4045	2575	1845		X	X*	X**	X**	X					81	465 & 470		HE120	
	90	4045	2575	1845		X	X*	X**	X**	X					81	465 & 470			WA1
	45	2380	1515	1085		X	X*	X**	X**	X					65	450			WA2
	86-UD	4050	2575	1850		X	X	X	X	X					747	2000 & 1400			AD1
		Maximum Square Footage Recommended per House Construction Type													General Filters	Herrmidifier	Research Products (Aprilaire)	Honeywell	Lobb

Model 60-BC1 is a free-standing, self-contained unit.

* When using this humidifier in this type heating system, reduce the maximum square footage (per construction) by 25%. ** When using this humidifier in this type heating system, reduce the maximum square footage (per construction) by 40%.